

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

| | | |
|-------------------------|-----------------------------------|--------------------------------|
| Ashland | Regulatory Information Number | 1-800-325-3751 |
| P.O. Box 2219 | Telephone | 614-790-3333 |
| Columbus, OH 43216 | Emergency telephone | 1-800-ASHLAND (1-800-274-5263) |
| Product name | PARTS PLUS ® SAE 15W-40 MOTOR OIL | |
| Product code | PP3403 | |
| Product Use Description | No data | |

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry skin and cause irritation.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Components | CAS-No. | Concentration |
|-----------------------------|----------------|----------------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | >=80-<90% |
| ZINC COMPOUNDS | 68649-42-3 | >=1.5-<5% |

4. FIRST AID MEASURES

Eyes

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Foam, Carbon dioxide (CO₂), Water mist

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons, hydrogen sulfide, oxides of sulfur, nitrogen and phosphorus, zinc oxide, Amines

Precautions for fire-fighting

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Spills of this material are very slippery.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Wash walking surfaces with detergent and water to reduce slipping hazard.

Other information

Notify the proper authorities as required that a spill has occurred. Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Exposure Guidelines

AROMATIC HYDROCARBON

| | | | |
|-----------|---|-------------|---------------------|
| OSHA Z1 | Permissible exposure limit | 500 ppm | |
| OSHA Z1 | Permissible exposure limit | 2,000 mg/m3 | |
| OSHA Z1A | time weighted average | 400 ppm | |
| OSHA Z1A | time weighted average | 1,600 mg/m3 | |
| US CA OEL | Time Weighted Average (TWA) Permissible Exposure Limit (PEL): | 400 ppm | |
| US CA OEL | Time Weighted Average (TWA) Permissible Exposure Limit (PEL): | 1,600 mg/m3 | |
| ACGIH | time weighted average | 5 mg/m3 | Mist. |
| ACGIH | Short term exposure limit | 10 mg/m3 | Mist. |
| ACGIH NIC | time weighted average | 0.2 mg/m3 | Inhalable fraction. |

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Physical state | liquid |
| Form | no data available |
| Colour | amber |
| Odour | hydrocarbon-like |
| Boiling point/boiling range | no data available |
| Melting point/range | no data available |
| Sublimation point | no data available |
| pH | no data available |
| Flash point | (>)199.00 °C Cleveland open cup |
| Ignition temperature | no data available |
| Evaporation rate | no data available |
| Lower explosion limit/Upper explosion limit | 1 %(V) / 6 %(V) |
| Particle size | no data available |
| Vapour pressure | 0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor Pressure |
| Relative vapour density | no data available |
| Density | 0.880 g/cm ³ @ 60.1 °F / 15.6 °C 7.4 lb/gal @ 60.1 °F / 15.6 °C |
| Bulk density | No data |
| Water solubility | negligible |
| Solubility | no data available |
| Partition coefficient: n-octanol/water | no data available |
| log Pow | no data available |
| Autoignition temperature | no data available |
| Viscosity, dynamic | no data available |
| Viscosity, kinematic | no data available |
| Solids in Solution | no data available |
| Decomposition temperature | no data available |
| Burning number | no data available |
| Dust explosion constant | no data available |
| Minimum ignition energy | no data available |

10. STABILITY AND REACTIVITY

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Stability

Stable

Conditions to avoid

excessive heat

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, oxides of sulfur, nitrogen and phosphorus

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg

ZINC COMPOUNDS : LD 50 Rat: 2,000 - 5,000 mg/kg

Acute inhalation toxicity

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Acute dermal toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50
Rabbit:
> 5 g/kg

ZINC COMPOUNDS : LD 50
Rabbit:
(>) 2,000 mg/kg

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

12. ECOLOGICAL INFORMATION

Biodegradability

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Bioaccumulation

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Ecotoxicity effects

Toxicity to fish

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to daphnia and other aquatic invertebrates.

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to algae

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to bacteria

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Biochemical Oxygen Demand (BOD)

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Chemical Oxygen Demand (COD)

HEAVY PARAFFINIC DISTILLATE : no data available
ZINC COMPOUNDS : no data available

Additional ecological information

HEAVY PARAFFINIC DISTILLATE : no data available
ZINC COMPOUNDS : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

No SARA Hazards

SARA 313 Component(s)

ZINC COMPOUNDS 1.59 %

New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
LUBRICANT ADDITIVE
AROMATIC HYDROCARBON
ZINC COMPOUNDS
ZINC COMPOUNDS 68649-42-3

PARTS PLUS ® SAE 15W-40 MOTOR OIL
PP3403

Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
LUBRICANT ADDITIVE
AROMATIC HYDROCARBON

Notification status

US. Toxic Substances Control Act y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)
Australia. Industrial Chemical (Notification and Assessment) Act y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand n (Negative listing)
Japan. Kashin-Hou Law List n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act y (positive listing)
China. Inventory of Existing Chemical Substances y (positive listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302) 62500 lbs

Reportable quantity-Components

ARSENIC 7440-38-2 1 lbs

| | HMIS | NFPA |
|------------------|-------------|-------------|
| Health | 1 | 1 |
| Flammability | 1 | 1 |
| Physical hazards | 0 | |
| Instability | | 0 |
| Specific Hazard | -- | -- |

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).