		Page: 1
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION


Product identifier
 Trade name : Auto Pride® MERCON V Automatic Transmission Fluid

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification
 Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

GHS label elements
 Hazard pictograms : 

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES	64742-54-7	Not a hazardous substance or mixture.	>= 30.00 - < 50.00
PETROLEUM DISTILLATES	64742-55-8	Not a hazardous substance or mixture.	>= 30.00 - < 50.00
PETROLEUM DISTILLATES		Not a hazardous substance or mixture.	>= 10.00 - < 20.00
POLYALKYLMETHACRYLATE		2A; H319	>= 10.00 - < 20.00
PETROLEUM DISTILLATES	64742-55-8	Asp. Tox. 1; H304	>= 1.00 - < 10.00
METHACRYLATE COPOLYMER		Eye Corr/Irr 2A; H319	>= 1.00 - < 10.00
ALKOXYLATED LONG-CHAIN ALKYL AMINE		Acute Tox. 4; H302 Skin Corr/Irr 1; H314 Eye Corr/Irr 1; H318	>= 0.10 - < 0.25

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid


Version: 2.0

795048

		<p>Skin Sens. 1B; H317</p> <p>Aquatic Acute 3; H402</p> <p>Aquatic Chronic 3; H412</p>	
ALKYL METHACRYLATE		<p>Skin Corr/Irr 2; H315</p> <p>Eye Corr/Irr 2A; H319</p> <p>Skin Sens. 1; H317</p> <p>STOT SE 3; H335</p> <p>Aquatic Acute 1; H400</p> <p>Aquatic Chronic 1; H410</p>	>= 0.10 - < 0.25
ALKYL ALKOXY AMINE		<p>Skin Corr/Irr 1B; H314</p> <p>Eye Corr/Irr 1; H318</p> <p>Aquatic Acute 1; H400</p> <p>Aquatic Chronic 1; H410</p>	>= 0.10 - < 0.25

SECTION 4. FIRST AID MEASURES


General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

		Page: 4
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
No symptoms known or expected.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Causes serious eye irritation.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

		Page: 5
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NOx)

Specific extinguishing methods : Standard procedure for chemical fires.

Product is compatible with standard fire-fighting agents.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES	64742-54-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
		TWA	5 mg/m3	CR OEL
PETROLEUM DISTILLATES	64742-55-8	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA	5 mg/m3	CR OEL
		PETROLEUM DISTILLATES		CMP (Mist)
CMP - CPT (Mist)	10 mg/m3 Mist			AR OEL
TWA (Mist)	5 mg/m3 Mist			PE OEL
STEL (Mist)	10 mg/m3			PE OEL

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

			Mist	
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA (Mist, inhalable)	5 mg/m3 Mist, inhalable	CR OEL
		STEL (Mist)	10 mg/m3 Mist	CR OEL
PETROLEUM DISTILLATES	64742-55-8	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA	5 mg/m3	CR OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : Wash hands before breaks and at the end of workday.

**SAFETY DATA SHEET**

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: red
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 190 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
	No data available
Lower explosion limit / Lower flammability limit	: No data available
	No data available
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.858 g/cm ³ (15.56 °C)
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: No data available

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

- Partition coefficient: n-octanol/water : No data available
- Decomposition temperature : No data available
- Viscosity
 - Viscosity, dynamic : No data available
 - Viscosity, kinematic : 34.6 mm²/s (40 °C)
- Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.
- Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
- Conditions to avoid : excessive heat
- Incompatible materials : alkalis
Strong acids
Strong oxidizing agents
- Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

- Acute oral toxicity : LD50 (Rat): > 15 g/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

PETROLEUM DISTILLATES:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

**SAFETY DATA SHEET**

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:**PETROLEUM DISTILLATES:**

Result: Slight, transient irritation

PETROLEUM DISTILLATES:

Species: Rabbit

Result: No skin irritation

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

POLYALKYLMETHACRYLATE:

Result: No skin irritation

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

METHACRYLATE COPOLYMER:

Result: No skin irritation

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: Corrosive

ALKYL METHACRYLATE:

Result: Irritating to skin.

ALKYL ALKOXY AMINE:

**SAFETY DATA SHEET**

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

Result: Corrosive after 3 minutes to 1 hour of exposure**Serious eye damage/eye irritation**

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

PETROLEUM DISTILLATES:

Result: No eye irritation

PETROLEUM DISTILLATES:

Species: Rabbit

Result: No eye irritation

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

POLYALKYLMETHACRYLATE:

Result: Irritating to eyes.

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

METHACRYLATE COPOLYMER:

Result: Irritating to eyes.

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: Corrosive

ALKYL METHACRYLATE:

Result: Irritating to eyes.

ALKYL ALKOXY AMINE:

Result: Corrosive**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

Components:**PETROLEUM DISTILLATES:**Test Type: **Buehler Test**Species: **Guinea pig**Assessment: **Does not cause skin sensitisation.****ALKOXYLATED LONG-CHAIN ALKYL AMINE:**Assessment: **The product is a skin sensitiser, sub-category 1B.****ALKYL METHACRYLATE:**Assessment: **May cause sensitisation by skin contact.****Germ cell mutagenicity**

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:**PETROLEUM DISTILLATES:**Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)****PETROLEUM DISTILLATES:**Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)****PETROLEUM DISTILLATES:**Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)****Reproductive toxicity**

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:**ALKYL METHACRYLATE:**Assessment: **May cause respiratory irritation.****STOT - repeated exposure**

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

Components:

PETROLEUM DISTILLATES:

No aspiration toxicity classification

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

PETROLEUM DISTILLATES:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l

PETROLEUM DISTILLATES:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF

SAFETY DATA SHEET

Revision Date: 04/12/2019

Print Date: 3/17/2020

SDS Number: R0394062

Auto Pride® MERCON V Automatic Transmission Fluid

Version: 2.0

795048

	Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Harmful to aquatic life.
Long-term (chronic) aquatic hazard	: Harmful to aquatic life with long lasting effects.

ALKYL METHACRYLATE:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard	: Very toxic to aquatic life with long lasting effects.

ALKYL ALKOXY AMINE:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard	: Very toxic to aquatic life with long lasting effects.

No data available


Persistence and degradability

Components:

PETROLEUM DISTILLATES:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

No data available

		Page: 15
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

Bioaccumulative potential

Components:

PETROLEUM DISTILLATES:

Partition coefficient: n-octanol/water : log Pow: **Expected > 7**

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good


IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

		Page: 16
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 04/12/2019

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

		Page: 17
SAFETY DATA SHEET		Revision Date: 04/12/2019
		Print Date: 3/17/2020
		SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid		Version: 2.0
795048		

H412 Harmful to aquatic life with long lasting effects.


Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative

	Page: 18
SAFETY DATA SHEET	Revision Date: 04/12/2019
	Print Date: 3/17/2020
	SDS Number: R0394062
Auto Pride® MERCON V Automatic Transmission Fluid	Version: 2.0
795048	

WEL : Workplace Exposure Level

CEATOX
 Assistance Center of the Institute of Toxicology
 Children's Hospital Clinic, Faculty of Medicine
 University of São Paulo.
 BR OEL : Occupational Exposure Limit (Brazil)
 UY OEL : Occupational Exposure Limit (Uruguay)
 PY OEL : Occupational Exposure Limit (Paraguay)