		Page: 1
SAFETY DATA SHEET		Revision Date: 04/19/2019
		Print Date: 3/17/2020
		SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil		Version: 3.0
884994		

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES	64742-54-7	Not a hazardous substance or mixture.	>= 70.00 - < 90.00
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 1.00 - < 10.00
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3	Skin Corr/Irr 3; H316 Aquatic Chronic 4;	>= 2.50 - < 10.00



SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

		H413	
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	Skin Sens. 1B; H317	>= 0.10 - < 1.00
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Skin Sens. 1B; H317	>= 0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray



SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

Foam
Carbon dioxide (CO2)
Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NOx)

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis



SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

DISTILLATES (PETROLEUM)	64742-65-0	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA	5 mg/m3	CR OEL
PETROLEUM DISTILLATES	64742-55-8	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA	5 mg/m3	CR OEL
MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM)		TWA (Inhalable fraction.)	5 mg/m3 Inhalable fraction.	UY OEL
PETROLEUM DISTILLATES	64742-54-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3	PA OEL

SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

			Mist	
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
		TWA	5 mg/m3	CR OEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 199 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper : 6 %(V)

**SAFETY DATA SHEET**

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

flammability limit	GLP: Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 0.055 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

Components:

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Acute oral toxicity : LD50 (Rat): > 16,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.


Components:

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

		Page: 8
SAFETY DATA SHEET		Revision Date: 04/19/2019
		Print Date: 3/17/2020
		SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil		Version: 3.0
884994		

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: **Rabbit**

Result: **Mild skin irritation**

Remarks: **Information given is based on data obtained from similar substances.**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Species: **Rabbit**

Result: **No skin irritation**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

PETROLEUM DISTILLATES:

Result: **No eye irritation**

PETROLEUM DISTILLATES:

Result: **No eye irritation**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: **Rabbit**

Result: **Slight, transient irritation**

Remarks: **Information given is based on data obtained from similar substances.**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Species: **Rabbit**

Result: **Slight, transient irritation**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):


Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

Method: **OECD Test Guideline 406**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Assessment: **The product is a skin sensitiser, sub-category 1B.**

		Page: 9
SAFETY DATA SHEET		Revision Date: 04/19/2019
		Print Date: 3/17/2020
		SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil		Version: 3.0
884994		

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment: **The product is a skin sensitiser, sub-category 1B.**

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: **Ames test**
 Test species: **Salmonella typhimurium**
 Metabolic activation: **with and without metabolic activation**
 Result: **negative**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: **Ames test**
 Test species: **Salmonella typhimurium**
 Metabolic activation: **with and without metabolic activation**
 Result: **negative**

Carcinogenicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

No aspiration toxicity classification

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Further information

Product:

SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

PETROLEUM DISTILLATES:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l

PETROLEUM DISTILLATES:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF

SAFETY DATA SHEET

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

Toxicity to algae : **EC50 (Pseudokirchneriella subcapitata (algae))**: 600 mg/l
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Toxicity to fish : **LL50 (Cyprinodon variegatus (sheepshead minnow))**: > 10,000 mg/l
Exposure time: **96 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 203**
Remarks: **Information given is based on data obtained from similar substances.**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea))**: > 1,000 mg/l
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 202**
Remarks: **Information given is based on data obtained from similar substances.**

Toxicity to algae : **NOEC (Pseudokirchneriella subcapitata (green algae))**: > 1,000 mg/l
End point: **Growth inhibition**
Exposure time: **96 h**
Test Type: **static test**
Test substance: **WAF**
Remarks: **Information given is based on data obtained from similar substances.**

No data available

Persistence and degradability**Components:**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **8 %**
Exposure time: **28 d**

No data available

Bioaccumulative potential**Components:**

PETROLEUM DISTILLATES:

Partition coefficient: n-octanol/water : log Pow: **Expected > 7**

**SAFETY DATA SHEET**

Revision Date: 04/19/2019

Print Date: 3/17/2020

SDS Number: 000000205480

Parts Plus® SAE 15W-40 PREMIUM Motor Oil

Version: 3.0

884994

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-octanol/water : log Pow: > 7.5

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Partition coefficient: n-octanol/water : log Pow: 10.9

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

		Page: 13
SAFETY DATA SHEET		Revision Date: 04/19/2019
		Print Date: 3/17/2020
		SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil		Version: 3.0
884994		

Chemical Control Order (CCO) : Not applicable
Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL
AICS : On the inventory, or in compliance with the inventory
ENCS : Not in compliance with the inventory
KECI : On the inventory, or in compliance with the inventory
PICCS : On the inventory, or in compliance with the inventory
IECSC : On the inventory, or in compliance with the inventory
TCSI : Not in compliance with the inventory
TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

Revision Date: 04/19/2019

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H316 Causes mild skin irritation.
H317 May cause an allergic skin reaction.
H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

		Page: 14
SAFETY DATA SHEET		Revision Date: 04/19/2019
		Print Date: 3/17/2020
		SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil		Version: 3.0
884994		

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :


ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology
Children's Hospital Clinic, Faculty of Medicine
University of São Paulo.

BR OEL : Occupational Exposure Limit (Brazil)
UY OEL : Occupational Exposure Limit (Uruguay)
PY OEL : Occupational Exposure Limit (Paraguay)

	Page: 15
SAFETY DATA SHEET	Revision Date: 04/19/2019
	Print Date: 3/17/2020
	SDS Number: 000000205480
Parts Plus® SAE 15W-40 PREMIUM Motor Oil 884994	Version: 3.0