		Page: 1
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid		Version: 3.0
PP3474		

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Parts Plus® DEX/MERC Automatic Transmission Fluid

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES	64742-54-7	Not a hazardous substance or mixture.	>= 90.00 - <= 100.00
PETROLEUM DISTILLATES	64742-55-8	Asp. Tox. 1; H304	>= 10.00 - < 20.00
PETROLEUM DISTILLATES		Not a hazardous substance or mixture.	>= 1.00 - < 10.00

SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid


Version: 3.0

PP3474

METHACRYLATE COPOLYMER		Eye Corr/Irr 2A; H319	>= 1.00 - < 10.00
ALKOXYLATED LONG-CHAIN ALKYL AMINE		Acute Tox. 4; H302 Skin Corr/Irr 1; H314 Eye Corr/Irr 1; H318 Skin Sens. 1B; H317 Aquatic Acute 3; H402 Aquatic Chronic 3; H412	>= 0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs

		Page: 3
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid		Version: 3.0
PP3474		

(i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

- acne
- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

Specific extinguishing methods : Standard procedure for chemical fires.

Product is compatible with standard fire-fighting agents.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,

SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid

Version: 3.0

PP3474

containment and cleaning up acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES	64742-54-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
		TWA	5 mg/m3	CR OEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid

Version: 3.0

PP3474

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : red
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 201 - 249 °C Method: Cleveland open cup
- Evaporation rate : > 1
Ethyl Ether
- Flammability (solid, gas) : No data available
- Upper explosion limit : 6 %(V)
GLP: Calculated Explosive Limit
- Lower explosion limit : 1 %(V)
GLP: Calculated Explosive Limit
- Vapour pressure : 0.0133333 hPa (21.11 °C)
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : No data available
- Density : 0.862 g/cm³ (15.56 °C)
- Solubility(ies)
Water solubility : No data available

SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid

Version: 3.0

PP3474

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 43 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**PETROLEUM DISTILLATES:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Acute oral toxicity : Assessment: The component/mixture is classified as acute oral toxicity, category 4.



SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid

Version: 3.0

PP3474

Skin corrosion/irritation

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

METHACRYLATE COPOLYMER:

Result: **No skin irritation**

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: **Corrosive to skin**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

PETROLEUM DISTILLATES:

Result: **No eye irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**


METHACRYLATE COPOLYMER:

Result: **Irritating to eyes.**

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Result: **Corrosive**

Respiratory or skin sensitisation

		Page: 8
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid		Version: 3.0
PP3474		

Skin sensitisation: Not classified based on available information.
 Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

ALKOXYLATED LONG-CHAIN ALKYL AMINE:

Assessment: **The product is a skin sensitiser, sub-category 1B.**

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

PETROLEUM DISTILLATES:

No aspiration toxicity classification

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

PETROLEUM DISTILLATES:

SAFETY DATA SHEET

Revision Date: 06/07/2018

Print Date: 3/17/2020

SDS Number: R0200299

Parts Plus® DEX/MERC Automatic Transmission Fluid

Version: 3.0

PP3474

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l

ALKOXYLATED LONG-CHAIN ALKYL AMINE:**Ecotoxicology Assessment**

Acute aquatic toxicity	: Harmful to aquatic life.
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.

No data available

Persistence and degradability**Components:**

No data available

Bioaccumulative potential**Components:****PETROLEUM DISTILLATES:**

Partition coefficient: n-octanol/water	: log Pow: Expected > 7
--	-------------------------

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available


Product:

Additional ecological information : No data available

Components:**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

		Page: 10
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid		Version: 3.0
PP3474		

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

UN_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION


Safety, health and environmental regulations/legislation specific for the substance or mixture

- Chemical Control Order (CCO) : Not applicable
- Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory

		Page: 11
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid PP3474		Version: 3.0

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/07/2018

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

		Page: 12
SAFETY DATA SHEET		Revision Date: 06/07/2018
		Print Date: 3/17/2020
		SDS Number: R0200299
Parts Plus® DEX/MERC Automatic Transmission Fluid		Version: 3.0
PP3474		

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology

Children's Hospital Clinic, Faculty of Medicine

University of São Paulo.

BR OEL : Occupational Exposure Limit (Brazil)

UY OEL : Occupational Exposure Limit (Uruguay)

PY OEL : Occupational Exposure Limit (Paraguay)