


| | | |
|--|--|---------------------------|
|  | | Page: 1 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

| | |
|---|---|
| Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com | Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825) |
|---|---|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute aquatic toxicity : Category 2

Chronic aquatic toxicity : Category 3

GHS label elements

Hazard pictograms : None

Signal word : None

Hazard statements : H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid


Version: 2.0

884996

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|---|-------------|---|--------------------|
| PETROLEUM DISTILLATES | 64742-55-8 | Not a hazardous substance or mixture. | >= 20.00 - < 30.00 |
| PETROLEUM DISTILLATES | 72623-86-0 | Asp. Tox. 1; H304 | >= 1.00 - < 10.00 |
| ORGANIC ACID ESTER | 125643-61-0 | Aquatic Chronic 4; H413 | >= 1.00 - < 10.00 |
| REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD. | | Acute Tox. 5; H303 Acute Tox. 4; H312 Skin Corr/Irr 1; H314 Eye Corr/Irr 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | >= 0.10 - < 1.00 |
| 4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate | 93882-40-7 | Eye Corr/Irr 2A; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | < 0.10 |


SECTION 4. FIRST AID MEASURES

| | | |
|--|--|---------------------------|
|  | | Page: 3 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

| | | |
|---|--|---------------------------|
|  | | Page: 4 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

- firefighting courses.
 - Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
 - Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Product is compatible with standard fire-fighting agents.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid : No materials to be especially mentioned.

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION


Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------------|------------|-------------------------------|--|--------|
| PETROLEUM DISTILLATES | 64742-55-8 | CMP (Mist) | 5 mg/m3 Mist | AR OEL |
| | | CMP - CPT (Mist) | 10 mg/m3 Mist | AR OEL |
| | | TWA (Mist) | 5 mg/m3 Mist | PE OEL |
| | | STEL (Mist) | 10 mg/m3 Mist | PE OEL |
| | | L-8/40 (Mist) | 5 mg/m3 Mist | VE OEL |
| | | LB (Mist) | 10 mg/m3 Mist | VE OEL |
| | | CPT (Mist) | 5 mg/m3 Mist | PA OEL |
| | | CCT (Mist) | 10 mg/m3 Mist | PA OEL |
| | | TWA | 5 mg/m3 | CR OEL |
| PETROLEUM DISTILLATES | 72623-86-0 | CMP (Mist) | 5 mg/m3 Mist | AR OEL |
| | | CMP - CPT (Mist) | 10 mg/m3 Mist | AR OEL |
| | | TWA (Mist) | 5 mg/m3 Mist | PE OEL |
| | | STEL (Mist) | 10 mg/m3 Mist | PE OEL |
| | | L-8/40 (Mist) | 5 mg/m3 Mist | VE OEL |
| | | LB (Mist) | 10 mg/m3 Mist | VE OEL |
| | | CPT (Mist) | 5 mg/m3 Mist | PA OEL |
| | | CCT (Mist) | 10 mg/m3 Mist | PA OEL |
| | | TWA | 5 mg/m3 | CR OEL |

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

| | | |
|--|--|---------------------------|
|  | | Page: 6 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

required.

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 350 °C (1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas
- Flash point : > 199 °C Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 6 %(V)
GLP: Calculated Explosive Limit
- Lower explosion limit : 1 %(V)
GLP: Calculated Explosive Limit
- Vapour pressure : 0.1333333 hPa (20 °C)
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : No data available
- Density : 0.849 g/cm³
- Solubility(ies)
Water solubility : No data available

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Thermal decomposition : No data available
- Viscosity
 - Viscosity, dynamic : No data available
 - Viscosity, kinematic : 36 mm²/s (40 °C)
 - 7 mm²/s (100 °C)
- Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.
- Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
- Conditions to avoid : excessive heat
- Incompatible materials : Strong oxidizing agents
- Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

ORGANIC ACID ESTER:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute dermal toxicity : LD50 (Rabbit): > 500 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
Assessment: The component/mixture is classified as acute dermal toxicity, category 4.

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Acute oral toxicity : LD50 (Rat, male): > 10,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**PETROLEUM DISTILLATES:**

**SAFETY DATA SHEET**

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

Species: **Rabbit**
Result: **No skin irritation**

PETROLEUM DISTILLATES:

Species: **Rabbit**
Result: **No skin irritation**

ORGANIC ACID ESTER:

Species: **Rabbit**
Method: **OECD Test Guideline 404**
Result: **No skin irritation**
GLP: **yes**

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

Result: **Corrosive to skin**

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Method: **EPISKIN Human Skin Model Test**
Result: **No skin irritation**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**PETROLEUM DISTILLATES:**

Species: **Rabbit**
Result: **No eye irritation**

PETROLEUM DISTILLATES:

Species: **Rabbit**
Result: **No eye irritation**

ORGANIC ACID ESTER:

Species: **Rabbit**
Result: **No eye irritation**
Method: **OECD Test Guideline 405**
GLP: **yes**

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

Result: **Corrosive**

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Species: **Rabbit**Result: **Irritating to eyes.****Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**PETROLEUM DISTILLATES:**Test Type: **Buehler Test**Species: **Guinea pig**Assessment: **Does not cause skin sensitisation.****PETROLEUM DISTILLATES:**Test Type: **Buehler Test**Species: **Guinea pig**Assessment: **Does not cause skin sensitisation.****ORGANIC ACID ESTER:**Test Type: **Maximisation Test**Species: **Guinea pig**Assessment: **Does not cause skin sensitisation.**Method: **OECD Test Guideline 406**Result: **Does not cause skin sensitisation.**GLP: **yes****REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:**Test Type: **Maximisation Test**Assessment: **Did not cause sensitisation on laboratory animals.**Method: **Directive 67/548/EEC, Annex V, B.6.**

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Test Type: **Buehler Test**Species: **Guinea pig**Assessment: **May cause sensitisation by skin contact.**Method: **OECD Test Guideline 406****Germ cell mutagenicity**

Not classified based on available information.

Components:**ORGANIC ACID ESTER:**Genotoxicity in vitro : Test Type: **Chromosome aberration test in vitro**

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

| | |
|----------------------|---|
| | Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative GLP: yes |
| | : Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes |
| Genotoxicity in vivo | : Test Type: In vivo micronucleus test Test species: Chinese hamster Method: OECD Test Guideline 474 Result: negative GLP: yes |

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

| | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Ames test Method: OECD Test Guideline 471 Result: positive |
| | : Method: OECD Test Guideline 473 Result: negative |
| Genotoxicity in vivo | : Test Type: In vivo micronucleus test Application Route: Oral Result: negative |

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

| | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Ames test Metabolic activation: with and without metabolic activation Result: negative |
|-----------------------|--|

Carcinogenicity

Not classified based on available information.

Reproductive toxicity


Not classified based on available information.

Components:

ORGANIC ACID ESTER:

| | |
|----------------------|--|
| Effects on fertility | : Species: Mouse Application Route: Oral Method: OECD Test Guideline 415 Result: Animal testing did not show any effects on fertility. GLP: yes |
|----------------------|--|

STOT - single exposure

| | | |
|--|--|---------------------------|
|  | | Page: 12 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Reproductive toxicity

Components:

ORGANIC ACID ESTER:

Species: **Rat, male and female**
 NOAEL: **5 mg/kg**
 Application Route: **Oral**
 Method: **OECD Test Guideline 407**
 GLP: **yes**

Aspiration toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

PETROLEUM DISTILLATES:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

PETROLEUM DISTILLATES:

Toxicity to fish : **LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l**
 Exposure time: **96 h**
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 203**
 Remarks: **No toxicity at the limit of solubility**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): > 10,000 mg/l**
 Exposure time: **48 h**
 Test Type: **static test**
 Test substance: **WAF**

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

| | |
|--|---|
| | Method: OECD Test Guideline 202 |
| Toxicity to algae | : NOEL (Pseudokirchneriella subcapitata (green algae)) : >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : NOELR (Oncorhynchus mykiss (rainbow trout)) : Calculated >= 1,000 mg/l Exposure time: 14 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEL (Daphnia (water flea)) : 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211 |

PETROLEUM DISTILLATES:

| | |
|--|--|
| Toxicity to fish | : LL50 (Pimephales promelas (fathead minnow)) : > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility |
| Toxicity to daphnia and other aquatic invertebrates | : EL50 (Daphnia magna (Water flea)) : > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202 |
| Toxicity to algae | : NOEL (Pseudokirchneriella subcapitata (green algae)) : >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : NOELR (Oncorhynchus mykiss (rainbow trout)) : Calculated >= 1,000 mg/l Exposure time: 14 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEL (Daphnia (water flea)) : 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211 |

ORGANIC ACID ESTER:

| | |
|------------------|---|
| Toxicity to fish | : LC50 (Danio rerio (zebra fish)) : > 100 mg/l |
|------------------|---|

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

| | |
|--|--|
| | <p>Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203</p> |
| Toxicity to daphnia and other aquatic invertebrates | <p>: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202 GLP: yes</p> |
| Toxicity to algae | <p>: EC50 (Desmodesmus subspicatus (green algae)): > 3 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes Remarks: No toxicity at the limit of solubility</p> <p>NOEC (Desmodesmus subspicatus (green algae)): >= 3 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes Remarks: No toxicity at the limit of solubility</p> |
| Toxicity to fish (Chronic toxicity) | <p>: NOEC (Danio rerio (zebra fish)): 0.001 mg/l Exposure time: 36 d Test Type: flow-through test Test substance: WAF Method: OECD Test Guideline 210 GLP: yes</p> |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | <p>: NOEC (Daphnia magna (Water flea)): ca. 0.01 mg/l Exposure time: 21 d Test Type: semi-static test Method: OECD Test Guideline 211 GLP: yes Remarks: No toxicity at the limit of solubility</p> |
| Toxicity to bacteria | <p>: EC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: Static Method: OECD Test Guideline 209 GLP: yes</p> |

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
 Exposure time: 96 h
 Test Type: static test

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

| | |
|--|--|
| | Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Water flea (Daphnia magna)): 0.09 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.31 mg/l Exposure time: 72 h Test Type: static test Method: Directive 67/548/EEC, Annex V, C.3. |
| M-Factor (Acute aquatic toxicity) | : 10 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC (Daphnia (water flea)): 0.14 mg/l Exposure time: 21 d |

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

| | |
|---|---|
| Toxicity to fish | : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h Test substance: WAF |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 0.062 mg/l Exposure time: 48 h Test Type: semi-static test |
| Toxicity to algae | : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test substance: WAF |
| M-Factor (Acute aquatic toxicity) | : 10 |
| M-Factor (Chronic aquatic toxicity) | : 1 |

No data available

Persistence and degradability

Components:

PETROLEUM DISTILLATES:

| | |
|------------------|--|
| Biodegradability | : Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B |
|------------------|--|

PETROLEUM DISTILLATES:

| | |
|------------------|---|
| Biodegradability | : Result: Not readily biodegradable. |
|------------------|---|

SAFETY DATA SHEET

Revision Date: 04/02/2018

Print Date: 3/17/2020

SDS Number: 000000207597

Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid

Version: 2.0

884996

Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

ORGANIC ACID ESTER:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: < 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: **yes**

REACTION PRODUCT OF ALKYLTHIOALCOHOL & SUBST. PHOSPHORUS CPD.:

Biodegradability : Inoculum: **activated sludge**
Biodegradation: 52.9 %
Exposure time: 60 d
Method: OECD Test Guideline 301B
Remarks: **Information given is based on data obtained from similar substances.**
The 10 day time window criterion is not fulfilled.
Not readily biodegradable.

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: 11 - 14 %
Exposure time: 28 d

No data available

Bioaccumulative potential**Components:****ORGANIC ACID ESTER:**

Bioaccumulation : Species: **Fish**
Bioconcentration factor (BCF): 260
Method: OECD Test Guideline 305
Remarks: **The substance has low potential for bioaccumulation.**

Partition coefficient: n-octanol/water : log Pow: **Calculated 9.2**

4,4'-thiodiethylenehydrogen -2-octadecenylsuccinate:

Partition coefficient: n-octanol/water : log Pow: **Expected < 4**

No data available

Mobility in soil**Components:**


No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.,

| | | |
|---|--|---------------------------|
|  | | Page: 17 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
| | | | | | |

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| |
|---------------------|
| Not dangerous goods |
| |

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| |
|---------------------|
| Not dangerous goods |
| |

INTERNATIONAL MARITIME DANGEROUS GOODS

| |
|---------------------|
| Not dangerous goods |
| |

UN_DG


| |
|---------------------|
| Not dangerous goods |
| |

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

| | | |
|--|--|---------------------------|
|  | | Page: 18 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

Revision Date: 04/02/2018

Full text of H-Statements

- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the

| | | |
|--|--|---------------------------|
|  | | Page: 19 |
| SAFETY DATA SHEET | | Revision Date: 04/02/2018 |
| | | Print Date: 3/17/2020 |
| | | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid | | Version: 2.0 |
| 884996 | | |

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CEATOX

| | |
|--|---------------------------|
|  | Page: 20 |
| SAFETY DATA SHEET | Revision Date: 04/02/2018 |
| | Print Date: 3/17/2020 |
| | SDS Number: 000000207597 |
| Parts Plus® IMPORT MULTI-VEHICLE Automatic Transmission Fluid 884996 | Version: 2.0 |

Assistance Center of the Institute of Toxicology
Children's Hospital Clinic, Faculty of Medicine
University of São Paulo.
BR OEL : Occupational Exposure Limit (Brazil)
UY OEL : Occupational Exposure Limit (Uruguay)
PY OEL : Occupational Exposure Limit (Paraguay)